



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GLOBAL GREASE EP 2

Multifunctional grease for all kinds of uses

DESCRIPTION

Lithium grease manufactured with high quality and purity mineral bases, and additives that improve its properties.

PERFORMANCE

STANDARDS: ISO – L – XBDHB 2

EP (extreme pressure) type grease for lubricating any mechanism that works at high loads and temperatures. Especially recommended in:

- Bearings subjected to intermittent loads and shocks.
- Points where a multifunctional EP grease is required.
- The EP (extreme pressure) additives it contains protect the mechanisms from wear under extreme loads.
- Excellent behaviour in mechanical work
- High resistance to ageing.
- High protection against metal part corrosion.
- Resistant to washing with water.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

APPEARANCE:	Brown	CONSISTENCY:	NLGI 2
THICKENER:	Lithium	DRIP POINT:	190°C / 374 F
PENETRATION AT 60 cycles:	295	4-BALL TEST:	315 Kg
PENETRATION AT 10⁴ cycles:	325		

Rev.11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

