GLOBAL GREASE ALG

Grease for agricultural machinery

DESCRIPTION

Lithium grease manufactured with high quality and purity mineral bases, and additives that improve its properties. Designed for use on Case, John Deere, International Harvester, etc. cotton harvesting machines.

PERFORMANCE

STANDARDS: ISO – L – XBDHA 00

- Excellent behaviour in mechanical work, improving its lubrication and reducing cotton contamination.
- Its soft consistency and very low base oil viscosity make it easy to start the combine at low temperatures.
- It protects spindles and bearings against wear.
- High protection against metal part corrosion.
- Resistant to washing with water.
- Usable from –20 to +120ºC continuously, with occasional temperatures of 140ºC being possible.
- Formulated to **John Deere** requirements for combine harvester grease.

TECHNICAL FEATURES

APPEARANCE:	Green	***CONSISTENCY:***	NLGI 00
THICKENER:	Lithium	***DRIP POINT:***	200ºC / 392 F
PENETRATION AT 60 cycles:	405	***4-BALL TEST:***	<160 Kg
PENETRATION AT 10^4 cycles:	-20 to +45		

Rev. 11/23

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

INNOVATIVE SME

ISO 9001
ISO 14001
BUREAU VERITAS
Certification